Product Design & Specifications

The professional choice in premium laser products

BTE-4E

Engraved Push Button Red Laser

635nm (Ruby Series)






Design & Operation

The Z-Bolt® BTE-4E is constructed of high quality steel & brass components and includes an IR filter and glass lens for superior laser performance. Jet black tube finish; engraves in vibrant gold (exposes brass casing). The BTE-4E also includes our special APC control circuit for power output stability (see below). Activate the momentary push button switch and the unit emits the highest power 635nm red laser light, projecting a brilliant ruby red laser dot. No comparison to cheaper 645~650nm red laser pointers, (the BTE-4E is twice as bright) the laser has a visible range of 4,500 ft. (Night) The red laser module operates on 2 pcs AAA batteries for superior battery life - fifteen (15) hours constant on operation. Ships in satin lined carry case; free lanyard & accessory end cap included.

The computerized APC diode drive circuit features "Automatic Power Control". The APC circuit is based on a photo diode feedback loop. The photo diode monitors the optical output and provides a control signal for the laser diode, helping to maintain the diode operation at a constant optical output level. The circuit adds to the lifetime of the laser, prevents overheating, and provides overall power output stability & efficiency.



Remove Cap Switch. Insert two AAA batteries (+) Tip toward cap. Replace Cap. Do not attempt to remove aperture; voids warranty.

Box Contents - Features

98% IR Filtering & Glass Focusing Lens (Not Plastic)
Battery Life - Fifteen Hours Constant On Operation
Computerized APC Diode Control Circuit
Power Source - 2 pcs AAA Alkaline
User Guide & Specification Card
Push Button Switch Activation
Satin Lined Carry / Gift Case
Accessory End Cap & Ring
36" Z-Bolt® Lanyard
Jet Black Finish

Z-Bolt.com/Guides

Laser Specifications

Length 5.70 in. x Diameter 0.51 in. (144 mm x 13 mm) Wavelength (Color) - 635 nm (Ruby Red) Output Power - 1.0~5.0 mW Diode Operating Life - 3,000 hours Diode Circuit Type - Computerized APC Beam Diameter at Source - 1.1 mm Output Mode - Constant Wave Range (Night) - 4,500 ft. FDA Safety Class - Illa ANSI Safety Class - 3R Warranty - 1 Year